



Technical Information

NO FRILLS 500/800 230V 50 Hz COMFORT/COMPACT





Utilisation

Water production


Standard Features


Reverse Osmosis Desalination for Seawater, brackish water and for cleaning of fresh water.

85-150 Litres/hour. 25°C Water temperature, 35.000 ppm* salinity.

COMFORT is modular, you can install the components, where space available. COMPACT is with all major components in a frame.NF 500/800: Membrane 2540 FR-80 SW 2540 Pressure vessel: Super Duplex, Membrane type: TFC (Thin film composite) Pre-filter 1+2 is mounted on a rack. Filter material: Polypropylene can be cleaned 3 times. FreshWater Flush system, Boost pump, Sea Water Filter and PH Stabilizer, built in cleaning circuit. *ppm= Parts per million (salinity)

DIMENSIONS mm










Frame, Front COMFORT+COMPACT Frame, Right side COMPACT Pre-Filte
Below: Pressure Vessel NF800 Motor + HP Pump, COMFORT

FWF System Boost Pump (LP Pump)











Seawater Inlet

3/4" hose. Sea -cock **must** be well under the waterline.

Seawater outlet

½" hose. Outlet must be over the waterline.

Voltage

230V 50Hz, 9,5A

Weight

ca. 70 Kg, dry

Water Quality

Less than 500 ppm* salt. Better than WHO standard. Minerals: 1-2%. 20% max in saltwater. (20 liters fresh water from 100 liters salt water)

Delivery

Ready to install. Manual - English or German.

Warranty

2 years for the system, 2 Years for the membrane, lifetime warranties for the pressure vessels.

Consumable Parts







Cleaning + preservation Kit Powder

Filter Kit